



CLEANING RECOMMENDATION FOR LOUVRES FOR ALL WASHABLE QUALITIES (WASHING MASHINE)



1. Loose the distance chains upwards from the bottom weights and remove the bottom weights.




2. Take the louvers at the slat holder out of the hooks. On removing the louvers please pay attention that the slats do not get any creases or tender spots.



3. Roll the slats up loosely and along the edges. Put up to 10 pieces in a tight fixed laundry bag for curtains into the washing mashine.



4. Choose washing programme up to max. 30°C temperature without spin-drying and add gentle washing powder, but regard absolutely that the powder you take is without any bleaching agents and whitener according to product information. If requested, you can put washing starche into the last rinse.



5. If the louveres do not dribble anymore, you can hang them back into the track, but without bending. Please fit the bottom weights into the seam and pin the link chains on.



6. The louvers dry on air while hanging in the rail without going out of shape. Please take care that the room is free of draught, solar radiation and heating condition.



7. If necessary, you can iron the slats with a steam iron with minimum heat and steam for cotton. Please iron along the edge of the slats. Please also consider our iron recommendation for louveres.

CLEANING RECOMMENDATION FOR LOUVRES FOR ALL WASHABLE QUALITIES (HAND WASHING)

Loose the distance chains upwards from the bottom weights and remove the bottom weights. Take the louveres at the slat holder out of the hooks.

On removing the louveres please pay attention that the slats do not get any creases or tender spots.

The slats should be rolled up lightly and straightly and put into a tank with soap suds, lying on the cutting edges. Appr. 10 to 30 slats can be put into one tank, with exception of the Alustar qualities. For those please take one tank per slat. Please pay attention that the tank you take is big enough to guarantee that the cutting edges are completely covered with water.

Water temperature max. 25 – 30°C. For Alustar Qualities up to 22°C.

For appr. 10 to 15 l water you need 40 ml liquid gentle washing agent, but regard absolutely that the agent you take is without any bleaching agents and whitener according to product information.

The slats should be soaked in the soap suds 15 to 60 minutes, only louveres made of cotton and linen should not lie more than 20 minutes in the water. By moving the slats in the soap suds from time to time you can reach a better washing result, but this is also not recommendable for the Alustar qualities.

Then please rinse the louveres in a water bath 2 to 3 times and let them drain appr. 30 minutes. If they do not dribble anymore, you can hang the louveres back into the track. Please take care that the room is free of draught, solar radiation and heating condition.

Please omit to remove dust or dirty marks etc. by rubbing or brushing etc., as this could lead to damaging the louveres. This is especially valid for the Alustar qualities, as the aluminium coating is really sensitive and could come off.

For our louveres which can be washed in the washing machine please observe the additional instruction.

IRON GUIDANCE

For louveres of all qualities which can be ironed (as per collection card)

Lay the single louveres lengthwise on the ironing board which must be covered with cotton or linen.

Please iron along the edge of the slats with a steam iron. Choose the minimum heat with minimum steam. Put the steam control on maximum position and observe that the water tank is always more than half-full.

Afterwards please lay one slat exactly on top of the other and let them cool down at least 1 hour before hanging them up resp. rolling them up along the edges.